PROTEGO® Cryogenic Tank Applications



Pilot operated valves that solve instability problems, such as fluttering and chattering, during operation. Cleaning for oxygen service available upon request. Cryogenic functional test available upon request. Low pressure and vacuum conservation vents. Full lift technology available (fully open with only 10% overpressure/pressure accumulation) Weight-loaded or spring-loaded Extremely low leakage rates on breather valves (much lower than ISO 28300 and API 2000 7th Ed.) Low pressure reducing valves


Quick-release bottom outlet valve with pneumatic actuator in-tank valves. Internal safety valves pneumatic and manual driven.

ATEX approved Flame Arresters End-of-line applications Deflagration Flame Arresters Endurance burning-proof Flame Arresters In-line applications Deflagration Flame Arresters Detonation Flame Arresters


Sold globally, serviced locally (PARC). Fully ATEX, ISO 9001, and ISO 14001 certified international company.




for safety and environment




Ammonia Storage Tank




Ethylene Storage Tank





LNG Storage Tank



PROTEGO® Application Examples

PROTEGO® Valves and Flame Arresters

Pressure/Vacuum Relief Valve: PROTEGO[®] PM-HF PROTEGO® VD/SV Pressure Relief Valve: PROTEGO[®] VN-A-PCPF-NV PROTEGO[®] ER/V Vacuum Relief Valve: PROTEGO® V/SV, V/SV-XL, V/SV-XXL Blanketing Valve: ZM-R In-Tank Valve: PROTEGO® NB/AP, ITV-S Internal Safety Valve: PROTEGO® SI/DP Detonation Flame Arrester: PROTEGO[®] DA-SB PROTEGO® DA-SB-T



Contact

PROTEGO[®] Team Tankequipment Thorsten Schaper phone.: +49 (0) 5307 / 809-167 e-mail: protegotankequipment@protego.com



